

24 VOLT PULSE CHARGER TWO STATION



TAMCN: TBD

ID: TBD

NSN: TBD

Functional Description

The 24V charger specifically designed to support (recharge and maintain) the Concorde battery in the 3K generator, part of the manufacturers requirement for maintaining the Concorde 24V battery is that it be recharged every 90 days. The 24V Dual will recharge and maintain up to two batteries at a time. It will also work on any other 24V battery (4HN) in the current inventory as well as any two 12V battery systems that are wired in series. The charger operates with an input voltage of 90/250AC at 50/60Hz and is reverse polarity protected. It automatically runs through its multistage charge and recovery process without input from the operator and is the first charger to operate in a "Green" mode when not actively charging using minimal electricity to maintain batteries in top condition.

Technical Description

Charger

Manufacturer: Pulse Tech
Model: 746x840

Power

Input: 100-250 VAC

Output:

Continuous Power: 24 Volts

Frequency (Hz): 50 / 60

Warranty

1 Year

Specifications

Dimensions

Length (in): 14.2
Width (in): 11.5
Height (in): 6.5
Weight (lbs): 10.5
Volume (ft³): .61

Temperatures

Operating: 32°F to + 122°F
0°C to + 50°C
Storage: -4°F to +194°F
-20°C to + 90°C

NOTES